

## CERTIFICATE OF QUALITY

### AWS A5.4 E307-16

**Product Features:**

1. Austenitic (non-magnetic) basic coated stainless steel electrode for joining and overlaying on manganese steels (up to 14% Mn).
2. Excellent welding performance in the vertical and overhead positions.
3. Weld metal contains 6.0% Mn provide high work hardening tendency and good crack resistance.
4. Easy slag removal and less spatter loss.

**Applications:**

Suitable for dissimilar metal joining or overlaying on Manganese steel to carbon steel casing or forgings.

**Guideline in Usage:**

1. 250~300°C x 1 hr baking prior to use.
2. Proper cleaning of welding groove or joint surface before welding and complete removal of spatter after welding
3. Recommending low electrical current for avoiding defects such as core wire overheat and coating peeling off.

**Guideline in Usage:**

1. 250~300°C x 1 hour baking prior to use.
2. Proper cleaning of welding groove or joint surface before welding and complete removal of spatter after welding
3. Recommending low electrical current for avoiding defects such as core wire overheat and coating peeling off.

**TYPICAL WELD DEPOSIT WEIGHT( % ):**

Dia (MM)	Chemical Composition (%)								
	C	Si	Mn	Ni	Cr	Mo	P	S	Ni
	<0.09	<0.32	5.2	9.82	18.88	0.1	0.018	0.006	Rem
3.2	Melting Metal Mechanical Performance								
	Tensile Strength(N/mm <sup>2</sup> )			Elongation (%)					
	640			43					

Quality Control Stamp:

Date: March-17, 2019

